Total Organic Carbon 150mg/L

93219-360	1 L	**35.25**
93219-540	4 L	**68.37**

Specifications

Total Organic Carbon . . . . . .147 - 153 mg/L
Traceable to NIST Standards.

Total Organic Carbon 100mg/L

93222-360	1 L	**35.25**
93222-540	4 L	**68.37**

Specifications

Total Organic Carbon . . . . . .98 - 102 mg/L
Traceable to NIST Standards

Total Organic Carbon 50 mg/L

93225-360	1 L	**35.25**
93225-540	4 L	**68.37**

Specifications

Total Organic Carbon . . . . . .48 - 52 mg/L
Traceable to NIST Standards.

26593-05	One Ampule each: 18, 180 NTU Model 18900	Set	**136.10**
26593-10	100 mL each: 18, 180 NTU Model 18900	Set	**122.49**
26593-00	500 mL each: 18, 180 NTU Model 18900	Set	**217.77**
26592-05	One Ampule each: 18, 180, 1800 NTU Ratio/XR, Ratio 2000	Set	**176.94**
26592-10	100 mL each: 18, 180, 1800 NTU Ratio/XR, Ratio 2000	Set	**190.55**
26592-00	500 mL each: 18, 180, 1800 NTU Ratio/XR, Ratio 2000	Set	**299.43**

Stannous Chloride, Crystals, Reagent, A.C.S.

$SnCl_2 \cdot 2H_2O$ FW 225.65
CAS: 10025-69-1

86388-140	100 g	**57.88**	6X100 g	**277.80**
86388-300	500 g	**193.88**	6X500 g	**930.60**
86388-380	2 kg	**567.63**	6X2 kg	**2724.62**
86388-580	10 kg	**1787.40**		

A.C.S. Specifications

Assay ($SnCl_2 \cdot 2H_2O$) . . . . . .98.0 - 103.0%
Solubility in HCl . . . . . .P.T.
Sulfate (SO_4) . . . . . .P.T.
Calcium (Ca) . . . . . .0.005% max.
Iron (Fe) . . . . . .0.003% max.
Lead (Pb) . . . . . .0.01% max.
Potassium (K) . . . . . .0.005% max.
Sodium (Na) . . . . . .0.01% max.

Stannous Oxide, Powder, Reagent

SnO FW 134.70
CAS: 21651-19-4

86480-140	100 g	**58.32**
86480-300	500 g	**137.55**

Specifications

Arsenic (As) . . . . . .0.001% max.
Chloride/ (Cl) . . . . . .0.01% max.
Iron (Fe) . . . . . .0.005% max.
Sulfate (SO_4) . . . . . .0.005% max.

Starch, Soluble, Powder, Reagent, A.C.S.

$(C_6H_{10}O_5)n$ FW (162.15)n
CAS: 9005-84-9

86602-140	100 g	**23.27**	6X100 g	**111.55**
86602-300	500 g	**69.97**	6X500 g	**335.17**

A.C.S. Specifications

Solubility in water . . . . . .P.T.
pH of a 2% solution @ 25°C . . . . . .5.0 - 7.0
Residue after ignition . . . . . .0.4% max.
Sensitivity . . . . . .P.T.